



GT-100 is designed with the capability to handle traditional heavy spreading as well as frequent light topdressing and is able to withstand and perform under the rigors of everyday use in all golf course environments.



Standard 9 HP engine with electric start.




Adjustable 15° tilt spinners allow for a 15' wide heavy, penetrating spread or a 30' swath of accurate coverage.



Standard in vehicle mount controls with independent conveyor and spinner shut off

SPECIFICATIONS

Model:	GT-100
Drive:	9 HP engine w/electric start
Hopper Capacity:	23 Cubic feet
Hopper Dimension:	20" x 50" at bottom and flares to 50" x 76" at top
Loading Height:	53"
Tire Size:	26.5" x 14-12 NHS turf tires
Box Construction:	11 Gauge galvanized steel with galvanized bolts
Standard Controls:	Independent conveyor and spinner shut off
	Optional vehicle mount control panel allowing for in vehicle electronic adjustment to conveyor and spinners for optimal delivery and precision depth.
Metering Gate:	Full manual adjustment from 0" to 7"
Conveyor Belt:	20" wide, smooth surface with in-line self tracking groove.
Hitch:	Heavy-duty SWIVEL pin hitch, to follow contours and undulations.
Topdressing Speed:	4 to 9 mph depending on conditions
Transport Speed:	Up to 15 mph empty
Empty Weight:	990 lbs.