## A SKIBO COMPANY ®




## **Rotary Rakes**

Pequea Rotary Rakes feature clean sweep raking widths from 9' to 13' allowing you to get the most from your hay crop efficiently. Each Pequea Rotary Rake features a hydraulic lift system and adjustable height to ease fieldwork and maximize maneuverability. The adjustable front cylinder allows users to fine tune the tine pitch; the HR1140 and HRS15 Pequea Rotary Rakes feature removable tine arms.







## HR930 HR1140 HRS15

- 9' (HR930), 11' (HR1140) or 13' (HRS15) Clean sweep raking width
- Removable tine arms (HR1140 & HRS15)
- Tandem axles with 4-bolt wheels (Standard)
- Exclusive Level-Lift hydraulics
- Totally enclosed oil bath gearbox (HR930 & HR1140)
- Sealed gearbox (HRS15)

Specifications	HR930	HR1140	HRS15
Working Width	10' 8"	13'	15'
Raking Width	9'	11'	13'
Transport Width	9' 4"	59"	100"
Gear Box	Enclosed Oil Bath	Enclosed Oil Bath	Sealed
Gear Reduction	7.9:1	7.9:1	9.7:1
Tine Arms	9	11	13
Double Tines per Arm	3	4	4
PTO HP Requirement	30 HP - 540 RPM	40 HP - 540 RPM	40 HP - 540 RPM
Hydraulic Requirement	6 GPM / 1200 psi - 1 Remote		1400 psi
Direction of Raking Action	Left	Left	Left
Weight	1050 lbs.	1550 lbs.	1900 lbs
Tandem Axles	Standard	Standard	Standard
Wheels & Tires	18.5 x 8 Flotation Tire / Painted Steel 4-Bolt Rim		

Pequea reserves the right to change specifications, design and price of products described in this literature without notice. © 2010 Pequea.