



Litter Spreaders

With nearly 20 years of manufacturing experience with limes, litter and fertilizer spreaders, you're looking at our accumulated knowledge and a solid spreading experience.



SP400 | SP450 | SP500 | SP550

- Transport lights
- Rear flood lights
- 16', 18', 20' and 22' hopper lengths
- Up to 580 cubic foot hauling capacity
- Truck mount or tandem axle configurations
- Hydraulic flow controls for quick, fine tuned adjustments of floor and spinner speeds
- Heavy duty 88k floor chain runs on lifetime poly tongue and groove flooring
- Heavy duty 25" spinner discs ensure a smooth and consistent spread pattern
- **See dealer for our full list of options**

Specifications	SP400	SP450	SP500	SP550
Hopper Length	16'	18'	20'	22'
Hopper Width (At Top)	96"			
Approx Overall Height (Depending on tire option)	90"			
Overall Length	26'	28'	30'	32'
Overall Width	97"		98"	99"
Capacity	10.7 cu yd (Struck) 16.7 cu yd (Heaped)	13.3 cu yd (Struck) 18.1 cu yd (Heaped)	14.8 cu yd (Struck) 19.6 cu yd (Heaped)	16.6 cu yd (Struck) 21.5 cu yd (Heaped)
Payload	20,000 lb	20,500 lb	24,000 lb	27,000 lb
Base Weight	6,000 lb	6,200 lb	6,400 lb	6,600 lb
Tires (See dealer for more options)	16.5L-16.1SL 10 Ply	16.5L-16.1SL 10 Ply	19L-16.1SL 10 Ply	21.5L-16.1SL 10 Ply
Floor & Chain	Heavy Duty 88K Chain on 3/4" Poly Tongue and Groove Floor			
Chain Width	35"			
Spinner Disc Diameter	25"			
Spinner Disc Thickness	1/4"			
Spin Paddles	6 Bolt on Reinforced			
Adjustable Spinners and Spinner Frame	Standard			

12/1/22 - Specifications subject to change without notice

