A SKIBO COMPANY ®



Manure Spreaders

With up to a 175 bushel capacity, Pequea manure spreaders are designed to withstand the demands of today's small farm. The manure spreader boxes are constructed of fully welded high strength, low alloy 10 gauge steel in 125 and 175 bushel capacity. Our large PTO model manure spreaders include 2 speed gearboxes, with a neutral and cleanout setting. Pequea manure spreader options include fine spread pans, top beaters, and hydraulic end gates.



125PTO 175PTO

Eight Aggressive Beaters:

- Offer wide and even spread pattern
- Engineered for maximum application
- Constructed of durable 1/4" steel
- Detachable for easy replacement if necessary



Specifications	125 PTO	175 PTO
Capacity	125 Bu. 90 Cu. Ft.	175 Bu.
Overall Length	16' 6"	17' 8"
Overall Width	76"	86"
Loading Height	45"	44"
Flared Width	56"	66"
Box Width	47"	54"
Box Length	128"	140"
Box Height	23"	24 1/2"
Box Construction	Fully Welded, High Strength - Low Alloy 10 Gauge	
Floor Construction	High Density Poly Vinyl 3/4" T & G	
Beater Paddles	8 Replaceable	10 Replaceable
Beater Diameter	26"	26"
Drive	PTO w/ 2 Speed Gearbox	
Apron Chain	7/16 T-Rod	
Spindle	2-1/8"	2-1/8"
Wheels/Tires	16 x 8-8 Bolt 10.00-16 lmp.	20 x 7-8 Bolt 10.00-20 Off-Road
Jack	2K	
Weight w/ Tires	1850 lbs.	2220 lbs.
Tongue Weight Empty	110 lbs.	180 lbs.
Tongue Weight Loaded	275 lbs.	330 lbs.
Horsepower Required	30 HP @ PTO	65 HP @ PTO

Pequea reserves the right to change specifications, design and price of products described in this literature without notice. © 2010 Pequea.