



# Orchard Spreaders

With nearly 20 years of manufacturing experience with limes, litter and fertilizer spreaders, you're looking at our accumulated knowledge and a solid spreading experience.



## GS8 | GS12 | V12 | V12G

- **Stainless Steel Optional**
- **Oil Cooler**
- **Dual Spinner**
- **Flicker Option**
- **Dual Conveyor**
- **Single Sided Conveyor**
- **See dealer for our full list of options**

V12 Shown

Specifications	GSN8	GS12	V12	V12G
Overall Height	76" - 82" Adjustable	67" - 73"	60"	70"
Overall Width	52"	77"	80"	
Overall Length	13' 2" - 13' 8"	16' 2"   18' 2"   20' 2"	20' - 20' 6"	
Hopper Width	52"	56"	72"	
Hopper Length	8'	8'   10'   12'	14'	
Floor Width	23 7/16"	31 3/8"		
Capacity	3.4 cu yd (Struck) 4.2 cu yd (Heaped)	4.25 cu yd (Struck) 6.25 cu yd (Heaped)	5 cu yd (Struck) 7.4 cu yd (Heaped)	7.8 cu yd (Struck) 10.5 cu yd (Heaped)
Payload	7,200 lb	13,000 lb	17,600 lb	
Empty Weight	2,000 lb	2,920 lb   3,140 lb   3,370 lb	4,000 lb	4,200 lb
Hydraulics	PTO Pump			
Flow Control	Hydraulic Adjustable Flow control			
Floor & Chain	667X Chain on 3/4" Poly Tongue and Groove Floor	Heavy Duty 88K Chain on 3/4" Poly Tongue and Groove Floor		
Axle	Single w/ Adj. Height Axle Hangars	Single w/ Adj. Height Axle Hangars	Tandem Walking Beam	
Tire & Wheel	12L x 15 x 10 Ply	16.5L x 16.1 x 14 Ply	18L x 16.1	
Power Requirements	45 HP	60HP	75 HP	

12/1/22 - Specifications subject to change without notice

