



Rotary Tedder



PEQUEA



Founded with spirit

Farming. There is no longer day, no harder work. It's a profession to be proud of. Pequea was founded in that spirit to benefit farmers everywhere.



Shaped by vision

We are committed to the future of farming. It is our vision to remain a leader in the industry, providing the best products we possibly can.



Built with pride

Building the best tedders is not just a job—it's our passion. We are proud of every piece of farm equipment that leaves our plant.

The five solid foundations of every tedder



Carbo-Austempered finger joints standard with ball bearings optimized pivot points

18.5" x 8" heavy duty tires come standard on a 4-bolt hubs with tapered bearings



Pivot pins on both are equipped with grease fittings, allowing for quick and easy lubrication

Internal view of rotary gearbox with hexagonal view



Front tilt cylinder adjusts rotor angle



46X



The 46X is a premium tedder at a value price. This tedder was designed with the essential features people love about Pequea's tedders: large tires for smooth field travel and fewer flats and real 4 bolt hubs with tapered bearing that last longer and allow for faster travel. The 46X has six flat bar tine arms per rotor and with asymmetrical tines on each arm. Heavy enclosed oil-bath commercial gearboxes are driven by a hexagonal shaft. At the pivot points, power is transferred through forged steel, carbo-austempered finger drives. Hydraulic fold and tilt are also standard, so there is to leave the tractor until the job is done.



Power is transferred through the pivots by forged, carbo-austempered finger drives that stay engaged when the tedder is folded for transport.


17' Working Width



Each rotor is supported by 18.5 x 8" implement Tired and real 4 bolt hubs with tapered bearings.



Hydraulic is standard on the 46X, like all Pequea Rotary Tedders, to create tine clearance on the go. A threaded rod on the cylinder allows for fine-tuned adjustment.



the 46X uses high-strength flat bar tine arms to hold six asymmetrical tines on each rotor.



HT4102



With an 18' 2" working width, the Model TT4102 is one of the widest 4-rotor tedders available. Built tough in North America, it sports these essential features: large tires for smoother field travel and fewer flats and real 4-bolt hubs with tapered bearings that last longer and allow for faster travel. The improved hydraulics enable quick folding and unfolding no ropes or latches are needed. All Pequea TurboTedders feature seven asymmetrical tines per rotor mounted on arms made from heavy pipe for durability. Heavy enclosed oil-bath commercial gearboxes include a 5 year warranty. At the pivot points, power is transferred through carbo-austempered finger drives to the rotors. Hydraulic fold and tilt are also standard, so there's no need to leave the tractor until the job is done.




The TT4102 was designed to make maintenance easy - with the hydraulic manifold mounted right next to the front tilt cylinder, it makes it simple to check or tighten hoses.


18'2" Working Width



Simple, reliable hydraulic system. The 4102 folds up quickly with just one cylinder on each side.



The TT4102 folds over center so no clumsy ropes or latches needed. Just fold and go.



Like all TT Series Tedders, the TT4102 features tubular tine arms. Tubular arms provide extra durability in the field. A shot-peened double tine slides over the arm for easy installation.



HT6201



TT6201 in transport position

Need something bigger than a 4-rotor tedder but still on a tight budget? The TT6201 was designed for those who need to maximize working width with a minimal amount of road travel. This tedder offers a 26' 6" working width and has the heavy-duty American made quality you want. All TurboTeddies™ feature seven asymmetrical tines per rotor mounted on arms made from durable pipe. Heavy enclosed oil-bath gearboxes include a **5 year warranty**. At the pivot points, power is transferred to the rotors through carburized finger drives. All of this rides smoothly atop the the patent pending "T-Flex" rubber torsion suspension. Hydraulic fold and and tilt are also standard, so there's no need to leave the tractor until the job is done.



The 6201 boasts a 26' 6" working width with 6 rotors. Dollar for dollar, it offers the most value in the tedder market.

26'6" Working Width



The TT6201 is the only tedder on the market with suspension under its rotors. The center two rotors on the 6201 feature "T-Flex," a patent-pending rubber torsion suspension that protect the spindle during transport and create a smoother ride in the field, increasing the durability of the tedder.

Like all TT Series Tedders, the TT6201 features tubular tine arms. Tubular arms provide extra durability in the field. A shot-peened double tine slides over the arm for easy install.



HT6 101



TT6101 in transport position

Need something rugged in the field and steady on the road? The TT6101 features a transport cart for quick travel if you're moving from field to field or farm to field and back. The six rotors offer a 26' 6" working width and the same heavy-duty American made quality you want. All TurboTeddars feature seven arms per rotor, with asymmetrical tines on arms made from heavy pipe, for durability. Enclosed commercial gearboxes include a **5 year warranty**. At the pivot points, power is transferred to the rotors through carbo austempered finger drives. Hydraulic fold and tilt are also standard, so there's no need to leave the tractor until the job is done.



11' 6" Transport Width

The 6101 model features a cart that the back of the tedder rests on when folded up – this allows for quick and safe road transport. Airplane tires on the cart keep the machine balanced during tedding and transport.


26'6" Working Width



The 6101 model transport cart has a built in suspension and helps prevent wrapping in long crops.



Automatic transport locks keep wheels from swiveling during transport while allowing freedom in the field.



Like all TT Series Tedders, the TT6101 features tubular tine arms. Tubular arms provide extra durability in the field. A shot-peened double tine slides over the arm for easy install.



HT8101



TT8101 in transport position

Pequea's biggest rotary tedder, the TT8101, has all the features you could want in a commercial tedder including carbo-austempered input gears, heavy duty 1-1/8" hexagonal driveshafts, and a 16NM Radial Pin Clutch PTO. This tedder is built to last. With a 35' working width, it will save you time and money. Like all of the TurboTeddors™ it also features seven arms per rotors, with asymmetrical tines on arms made from heavy pipe for durability. Heavy enclosed commercial gearboxes include a 5 year warranty. At the pivot points, power is transferred efficiently to the rotors through carbo-austempered finger drives. Hydraulic fold and tilt are also standard, so there's no need to leave the tractor until the job is done.



The 8101 model features a cart that the back of the tedder rests on when folded up – this allows for quick and safe road transport. Airplane tires on the cart keep the machine balanced during tedding and transport.

35' Working Width



The 8101 model transport cart has a built in suspension and helps prevent wrapping in long crops.



Automatic transport locks keep wheels from swiveling during transport while allowing freedom in the field.



Like all TT Series Tedders, the TT8101 features tubular tine arms. Tubular arms provide extra durability in the field. A shot-peened double tine slides over the arm for easy install.

General Specifications




Rotary Tedders

The TurboTedder™ is Pequea's solution for gentle yet fast hay crop management. Pequea TurboTedder rotary tedders are available in 2-rotor, 4-rotor, 6-rotor and 8-rotor models with seven tine arms per rotor. In the tedding position, the tines remain level for a clean, efficient sweep action. If you need a heavy-duty rotary tedder that gets the job done, make the North American Pequea TurboTedder your choice.

26X | 46X | TT4102 | TT6201 | TT6101 | TT8101

- Fully enclosed gear boxes
- Standard tilt cylinder
- Heavy-duty hubs with four bolt rims
- Full hydraulics for tilt and transport (TT2100 tilt only)
- Large dish and 7 heavy pipe arms per rotor

| Specifications | 26X | 46X | TT4102 | TT6201 | TT6101 | TT8101 |
|----------------------------|------------------------------|------------------------------|------------------------------|------------------------------|------------------------------|------------------------------|
| Working Width | 9'2" | 17' | 18' 2" | 26' 6" | 26' 6" | 35' |
| Transport Width | - | 8' 9" | 9' 2" | 9'2" | 11' 6" | 11' 6" |
| Number of Rotors | 2 | 4 | 4 | 6 | 6 | 8 |
| Tine Arms Per Rotor | 6 | 6 | 7 | 7 | 7 | 7 |
| Linkage | Trailed | Trailed | Trailed | Trailed | Trailed | Trailed |
| Tedder Rotor Tire Size | 18.5 x 8 | 18.5 x 8 | 18.5 x 8 | 18.5 x 8 | 18.5 x 8 | 18.5 x 8 |
| Transport Cart Tire Size | N/A | N/A | N/A | N/A | Aircraft Tire | Aircraft Tire |
| Weight (lb) | 700 lb | 1050 | 1350 | 2150 | 3100 | 3700 |
| Hydraulic Requirement | - | 1000 psi | 1000 psi | 1300 psi | 1200 psi | 1350 psi |
| Hydraulic Port(s) Required | 1 | 1 | 1 | 2 | 2 | 2 |
| Min. HP @ PTO | 25 | 30 | 30 | 45 | 45 | 55 |
| Rotor Gear Box Lubrication | Enclosed Grease | Enclosed Grease | Enclosed Grease | Enclosed Grease | Enclosed Grease | Enclosed Grease |
| Center Gearbox Lubrication | Oil Bath | Oil Bath | Oil Bath | Oil Bath | Oil Bath | Oil Bath |
| Tine Arm Material | Pipe | Flat Bar | Pipe | Pipe | Pipe | Pipe |
| Overall Transport Length | - | 9' 8" | 9' 8" | 9' 8" | 17' 3" | 19' 9" |
| Rotor Spindle Wheel Hub | 4-Bolt with Tapered Bearings | 4-Bolt with Tapered Bearings | 4-Bolt with Tapered Bearings | 4-Bolt with Tapered Bearings | 4-Bolt with Tapered Bearings | 4-Bolt with Tapered Bearings |
| Transport Lights | N/A | N/A | N/A | N/A | Optional | Optional |



TRADITION IN PROGRESS

