

PEQUEAD



A Skibo Company



Founded with spirit

Farming. There is no longer day, no harder work. It's a profession to be proud of. Pequea was founded in that spirit to benefit farmers everywhere.



Shaped by vision

We are committed to the future of farming. It is our vision to remain a leader in the industry, providing the best products we possibly can.



Built with pride

Building the best tedders is not just a job—it's our passion. We are proud of every piece of farm equipment that leaves our plant.


What Pequea offers you in every spreader



Get more value for your money

Simple and easy to operate and maintain





A poly floor and T-rod chain makes these spreaders durable and long lasting

Strong and durable 1/4" beater paddles, fully welded high strength steel box



25G/35G

The 25 and 35 ground drive are ideal for the equine enthusiast or the sundowner farmer who lacks a tractor or needs to get in tight areas to clean up manure. With the ability to be pulled by a quad or UTV the Pequea spreaders bring more to the table than their price point competition, a lot more.

The solid axle and dual drive ratcheting hubs allows the web and the beater to be driven either wheel or both. So even if you lose traction with one tire or are in a small field making lots of turns you will still get an even spread pattern. T-rod chain, poly tongue and groove floor, and fully welded unibody construction give you the strength and durability you want. Pequea spreaders are strong, reliable, and easy to operate helping you get the job done right. Also available are optional urethane lining, manual end gate, and fine spread pan.



Easy to operate engagement levers engage the solid axle and dual drive hubs are important on all ground drive spreaders for sure footed traction.





Standard with fold up sidewind jack

9' 6" - 11'6" Overall Length



The poly tongue and groove floor and t-rod chain are designed for a long life and easy maintenance

Heavy duty replaceable paddles

50G/50P

Need more capacity? 50 bushel units are available in either PTO or ground drive depending on your needs. Heavier T-rod chain and poly floors are standard as well as the fully welded unibody construction. Flared tops add strength, capacity, and helps keep the manure where it should be; in the spreader during loading and travel.

The PTO unit is driven by a short belt (for shear protection) to the solid shaft held by bearings running the length of the side to an enclosed gearbox. The ground driven units offer oversized drive components and drive chain along with a positive traction axle and ratcheting hubs for long life and ease of maintenance. Options available on these units are: manual end gate, urethane lining, and fine spread pan.







16' 6" Overall Length



Optional fine spread pan helps keep fine material in the spreader traveling to and from fields

Low maintenance 7/16" t-rod chain along with tongue and groove poly floor

80P

So, you have more animals and manure but want to make less trips to the field? The 80 PTO is the largest offering from Pequea in a compact spreader. It has the same features as the 50 PTO but in a larger capacity and more robust build.

The heavier 7/16" t-rod chain, spindles and larger tires help you move more manure faster but still allow maneuverability and ease of loading for your operation. A top beater is also available on the 80 PTO to help spread pen packed manure. Additional options are the urethane lining, manual end gate, and a fine spread pan.







Optional top beater for breaking up tough pen packed manure

20' 5" Overall Length



Simple and durable drive system keeps you going for the long haul

Drive belt acts as shear protection

General Specifications



Compact Spreaders

Pequea brings 50 years of experience to the development, design and production of our line of box manure spreaders. Pequea is committed to building high quality box manure spreaders at a fair price. We offer a variety of different sizes and options to suit your specific spreading needs.

Options

- Top Beater (80P Only)
- Manual End Gate (All Models)
- Fine Spread Pan (All Models)
- lack w/Wheel

Specifications	25G	35G	50G	50P	80P	
Capacity Heaped	25 Bu.	35 Bu.	50 Bu.	50 Bu.	80 Bu.	
Capacity Struck CF	18 cu. ft.	25 cu. ft.	36 cu. ft.	36 cu. ft.	57 cu. ft.	
Overall Width	51″		57"	54"	63.5"	
Overall Length	10′ 1″	11′ 11″	12' 6"		14′ 5″	
Loading Height	30"		35″		39"	
Box Flared Width	34"		43"		47-1/2"	
Box Construction	12 Gauge High Strength Steel					
Box Width	28"		36"		40"	
Drive	Ground Drive PTO wi			PTO with 1 S	1 Speed Gearbox	
Beater Paddles (Bolt On)	8					
Beater Diameter	18"		20"			
Floor Construction	High Density 3/4" Tongue & Groove Poly Vinyl					
Apron Chain	5/16" T-Rod 7/16" T-Rod				7/16" T-Rod	
Jack	1000 lb Side Wind			2000 lb Side Wind		
Weight	425 lb	575 lb	950 lb	1,000 lb	1,125 lb	
Tongue Weight Empty	35 lb	45 lb	60 lb	60 lb	60 lb	
Spindle	1-1/4"		1-3/8"	1-5/8"	1-3/4"	
Horsepower Required		N/A		15 HP	18 HP	
Tire	6 x 12 Traction Tire		7 x 14 Traction Tire	6.40 x 15 Implement Tire	9.50 x 15 Implement Tire	



A Skibo Company