



Lime Spreaders

With nearly 20 years of manufacturing experience with limes, litter and fertilizer spreaders, you're looking at our accumulated knowledge and a solid spreading experience.



SL6 | SL10

- 4 Tire + Wheel Options for SL10
- Heavy Duty Axle Assembly for SL10
- Stainless Steel is Optional on SL6 and SL10
- Web Slats Configuration Optional SL6 and SL10
- Fertilizer Package Option for SL6 and SL10
- CV PTO Shaft Optional on SL6 and SL10
- 1000 RPM PTO Shaft Option on SL10
- See dealer for our full list of options

Optional Stainless Steel SL10

Specifications	SL6	SL10
Overall Height	81"	92"
Overall Width	73"	96"
Overall Length	17' 3"	20'
Hopper Width	70"	75"
Hopper Length	9'	11'
Floor Width	23 3/8"	31 3/8"
Capacity	5.2 cu yd (Struck)	8.9 cu yd (Struck)
Payload	12,000 lb	20,000 lb
Empty Weight	4,000 lb	6,000 lb
Spinner Disc Diameter	25"	
Flow Control	Hydraulic Adjustable Flow control	
Floor & Chain	667X Chain on 3/4" Poly Tongue and Groove Floor	
Axle	Heavy Duty Tandem Axle	
Tire & Wheel	12.L x 15 x 12 Ply	
Optional	Digistar or Raven System	
Power Requirements	60 HP	

12/1/22 - Specifications subject to change without notice

